



●寸法表

種類	呼び	寸法 mm								配筋				参考重量 (kg)	スパン (mm)	曲げ強度荷重 KN									
		b	b ₁	t	t ₁	t ₂	l	r	b ₂	縦鉄筋 径又は 呼び	数量 (本)	横鉄筋 径又は 呼び	数量 (本)												
1 種	150	210	35	35	30	5	600	15	75	2.60	3	2.60	5	10	180	5									
	180	250	40	40	35	10											18	90	3.20	4	3.20	6	14	210	6
	240	330	50	45	40																				
	300	400	55	60	50	10			120	5.00	6	6	33				350	10							
	360	460	60	65	55	150			6										78	670					
	450	560	75	75	65	180				150	6	78	670												
	600	740	75	75	65	150			6								78	670							
2 種	150	210	35	90	80	10	600	15		75	D6※	3	D6※	7	26	180			45						
	180	250	40	100	85	15			90								5	D10		5	31	210	40		
	240	330	50																					100	85
	300	400	55	180	120	20			120	7	7	64	410												
	360	460	60											120			100	20		150	D10	6	93	500	40
	450	560	75	150	130	20			150	D13	6	156	670	45											
	600	740	75	150	130	20			150								D13	6		156	670	45			

注) ※ JIS G3112に規定する呼びD6の棒鋼の代わりに、JIS G3532に規定する線径6.00mmの普通鉄線又は線径6.00mm若しくは公称線径6.00mmのコンクリート用鉄線を使用してもよい。